



Processing Aid Application Form

Strictly Confidential

Please return form to:
 Approval Operations (Foods)
 SEAC
 Unilever
 Colworth House
 Sharnbrook,
 Bedfordshire MK44 1LQ
Fax: +44 (0)1234 264711
E-mail: Toxicology-URC.SEAC@unilever.com

For Official Use Only: Reference Number	
--	--

Complete all details in **ENGLISH** and use **CAPITAL** letters. Tick (+) the appropriate boxes.

Applicant Details

Applicant Name:	AIMOL-M B.V.
Company Name and Address:	AIMOL-M B.V., Haringvliet 543 3011 ZP Rotterdam The Netherlands E-mail: pg@aimol.nl tel.+31.10.2827927 fax +31.10.2827926
Request Title:	
Company Reference:	
Previous SEAC Reference:	
Division:	Foods <input checked="" type="checkbox"/>
Corporate Category:	Food grade lubricants

General Information

Processing Aid Name:	AIMOL-M Foodmax Grease ASP 2
Manufacturer Name:	AIMOL-M B.V., Haringvliet 543 3011 ZP Rotterdam The Netherlands E-mail: pg@aimol.nl tel.+31.10.2827927 fax +31.10.2827926

Manufacturer Contact Details: Name, Telephone and/or Fax and/or e-mail

Processing Aid Application Form

AIMOL-M B.V., Haringvliet 543 3011 ZP Rotterdam The Netherlands E-mail: pg@aimol.nl
tel.+31.10.2827927 fax +31.10.2827926

General Information (continued)

Alternative names/synonyms, other references (if any known) for the processing aid:

Food Grade approvals (type H-1- for the lubricants with incidental contact with food) received from InS and NSF companies. A lot of referencies from the final customers including Pepsi company (Russia), Nivoba (Holland), Welcon AS (Norway) etc

If this is a mixture please list the Component(s) Name and CAS Number(s):

Component Name:	CAS Number:
See MSDS in attached file	

Use

Explain in full how it is used and what is its function?

AIMOL-M Foodmax Grease ASP 2 is an aluminum complex greases designed for the lubrication of almost any application which requires a food grade lubricant. AIMOL-M Foodmax Grease ASP 2 is formulated with complex soap, synthetic base oils, additive package and authorized solid lubricants. They are provided with excellent lubricating properties and a high water resistance, they are perfect when a combination of water resistance and high loads are required. Thanks to their superior resistance to water they are very suitable for the lubrication of chains operated in very wet conditions such as food conveyor chains (packing industry & slaughter houses for example). General Applications:

Applications:

- General lubrication and bearings in the food industry
- Slideways, chains etc.
- Water valves and tap lubrication
- Bearings exposed to medium load and high temperatures from -40 to 180°C

Processing Aid Application Form

Maximum level at which it will be used?

As all Food Grade lubricants (type H-1) the max level is 10 ppm

Confirm that the processing aid is either removed physically from the foodstuff or destroyed during the processing?

YES

NO

If YES, give full details here

What is the residual level of the processing aid in the final food?

0 ppm

Regulatory Support

Are you aware of any regulatory approval for food contact (directly or indirectly)?

Yes

No

Are you aware of any history of use of this material in the food industry?

Yes

No

Additional Information

Supply any other information which is relevant to this application?

The additional information you can receive from technical data sheet or from managing director of AIMOL-M company Pieter de Groot pg@aimol.nl tel.+31.10.2827927

Processing Aid Application Form

Will the food produced by this process be used in consumer test?

Yes

If YES, complete the **Consumer Test Form**

No